

EXIT Exit Signs

Certification Number:

EXPLOSIONPROOF

For UL.60079-1 Standard Class I,II Div.1 and 2 Groups C,D,E,F and G

For IEC.60079-0 to 1 Standard Zone 1 and Zone 2



TIS 1955-2542

มีสินค้าพร้อมส่ง!

ติดต่อ คุณปัด 081-2345542

Technical data:

Explosion Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079-1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP54 / 66 acc. To IEC 60529
Ambient Temp. (Ta)	: - 5 °C to + 55 °C
Rated Voltage	: 220 - 240 V AC 50/60Hz.
Lamp	: 1 x 10w. For Flu. , 1 x 26w. For Compact Flu.
LED Life	: 35000 Hrs.
LED Watt. (NEW PRODUCT)	: 20 x 0.5w. (10w.)
Battery	: 6V. 4Ah (Flu. and Compact Flu.)
	: 3.6V. 2.1Ah (LED)
Recharge time	: 24-hours from fully discharge (Halogen Lamp)
	: 10-12-hours from fully discharge (LED)
Emergency duration	: 2-hours (Flu. and Compact Flu.) , 3-hours (LED)
Entries thread	: 3/4" NPT
Protection class for UL	: Class I, Division 1 or 2 Group. C,D
	: Class II, Division 1 or 2 Groups. E,F,G
	: Class III
Protection class for IEC	: Zone1 , 21 and Zone 2 , 22

Specification:

Body material	: Marine grade copper-free aluminum alloy with epoxy-polyester powder coated , RAL7032(GREY)
Lens	: Heat and impact resistant clear glass
Sing face	: White, Green acrylic with red, white color letters.

Catalogue Numbers:



Lamp Watts	Temp. Class (Surface Temp.)		Cat. No.
	40 °C Ta	55 °C Ta	
LED LAMP			
20 x .5w. (10w.)	T6	T6	EXIT2010L

